

## Cool sounds, attractive street style.

Leave your house and take an extra portion of your favourite sounds with you. Or just relax and enjoy funky beats from your own hi-fi system at home. The new HD 400 models from Sennheiser offer all that – and a lot more besides. Their feelgood sound is accompanied by new, stylish designs. The HD 419, HD 429 and HD 439 feature a punchy bass, while the HD 449 guarantees a detailed, balanced sound image.

Made for ☐ iPhone ☐ iPad



HD 449 Sennheiser's HD 449 stands out from the crowd with its striking, kink design and high-quality audio reproduction. Delivering detailed sound and clarity, both indoor and outdoor with its advanced acoustic system, these headphones are guaranteed to please. Its design ensures a comfortable fit around your ears and isolate against ambient noise. Completing the package are gold plated plugs, extension cable and adaptor for excellent connectivity anywhere.

- Advanced acoustic system with powerful neodymium magnets and lightweight diaphragms for a lifelike stereo sound experience
- Closed circumaural headphone design isolate against ambient noise
- Ergonomic design provides a comfortable fit
- Gold plated plugs and 6.3mm stereo adaptor for excellent connectivity, with home Hifi equipment
- Carrying pouch and extension cable for protection and added length
- Optimised for portable audio including MP3, CD players, iPad, iPod and iPhone (iPad, iPhone and iPod are trademarks of Apple Inc., registered in the U.S. and other countries.)
- 2-year warranty





HD 439 For a combination of street style and prowess, the HD 439 closed-back stereo headphones are the choice. These headphones offer you the world of audio with a bold and revolutionary design, including a chrome inner lining and black mesh turbines. Delight in an enhanced and outstanding bass performance. Featuring two detachable single-sided cables, you will be able to find the cable length that distinguishes you apart from others. Make a firm statement with the HD 439 and feel the difference.

- Powerful neodymium magnets for an enhanced bass experience
- Closed circumaural headphone design isolate against ambient noise
- Ergonomic design provides a comfortable fit
- Choice of two single-sided cables for flexible length and convenience
- Optimised for portable audio including MP3, CD players, iPad, iPod and iPhone (iPad, iPhone and iPod are trademarks of Apple Inc., registered in the U.S. and other countries.)
- 2-year warranty



HD 429 The HD 429 features a powerful bass response provided by high-output neodymium magnets. In addition, these headphones display an innovative and ergonomic, silicone design, providing durability and a comfortable fit, every single time. Their closed circumaural headphone configuration effectively isolate against ambient noise, while the single-sided cable reduces tangling. Stand out and be different with the audio quality you deserve.

- High-output neodymium magnets for stereo sound with smooth bass response
- Closed circumaural headphone design isolate against ambient noise
- Ergonomic design provides a comfortable fit
- Single-sided cable for freedom of movement
- Optimised for portable audio including MP3, CD players, iPad, iPod and iPhone (iPad, iPhone and iPod are trademarks of Apple Inc., registered in the U.S. and other countries.)
- 2-year warranty



HD 419 The HD 419 headphones are a fusion of attractive aesthetics with a powerful punchy, dynamic bass. With its closed circumaural design, you can expect efficient isolation of ambient noise making it friendly in all environments. In addition, their special single-sided cable, eliminates tangling, ensuring comfort and usability. The HD 419 is an ideal companion for your all-day audio pleasures.

- Powerful neodymium magnets for stereo sound with powerful punchy bass
- Closed circumaural headphone design isolate against ambient noise
- Single-sided cable for freedom of movement
- Optimised for portable audio including MP3,
   CD players, iPad, iPod and iPhone (iPad,
   iPhone and iPod are trademarks of Apple Inc.,
   registered in the U.S. and other countries.)
- 2-year warranty







App	
<del>/</del> c	
S	
arl	
em	
g	
e t	
aĽ	
aq	
and iP	
au	
e	
ho	
≘ੑ	
po,	
≔	
Ε	
<u></u>	
er.	
eis	
چّ	
v.senn	
S.	
⋛	
≨	
_	
bH & Co. KG	
ö	
ر حم	
Ĭ	
a e	
Ġ	
٦	
ò	
₹	
<u> </u>	
<u>.</u>	
ise	
å.	
틸	
Se	
ırk of Se	
논	
na	
ē	
ğ	
Ξ.	
ē	
ţ <u>.</u>	
gis	
ē	
а	
. <u></u>	
sel	
ē	
ב	
ē	
<del>.</del>	
Germany	
пa	
e.	
9	
Ξ.	
tec	
Ξ	
ቯ	
08/11 Print	
×1	
80	
,6 08/	

/	HD 449		HD 439	
	Version West	Version East	Version West	Version East
EAN	4044155071634	4044155071627	4044155071610	4044155071603
UPC	615104218093	615104218086	615104218079	615104218055
Article No.	504767	504766	504765	504764
Transducer principle	Dynamic, closed		Dynamic, closed	
Frequency response	16 – 24000 Hz		17 – 22500 Hz	
Sound Pressure level	114 dB (1 kHz / 1 V <sub>rms</sub> )		112 dB (1 kHz / 1 V <sub>rms</sub> )	
Impedance	32 Ω		32 Ω	
THD	< 0.1 % (1 kHz / 100 dB)		< 0.1 % (1 kHz / 100 dB)	
Cable / Plug	1.4 m single-sided OFC cable with 1.6 m extension cable with 3.5 mm gold straight plug / 6.3 mm gold adaptor plug		1.4 m and 3 m single-sided detachable OFC cables with 3.5 mm gold straight plug / 6.3 mm gold adaptor plug	
Delivery includes	HD 449 headphones, 6.3 mm adaptor plug		HD 439 headphones	
Packaging				
Dimension of product packaging (W x H x D)	204 x 93 x 240 mm		204 x 93 x 240 mm	
Dimension of outer master carton (W x H x D)	425 x 305 x 263 mm		425 x 305 x 263 mm	
Amount of products per outer master carton	6		6	
Languages on product packaging	Version West: English, French, Spanish, Portuguese, German, Italian, Dutch Version East: English, Russian, Polish, Turkish, Chinese short, Chinese long, Korean			

EAN         Version West         Version East         Version West         Version East           EAN         4044155071597         4044155071580         4044155071573         4044155071566           UPC         615104218048         615104218031         615104218024         615104218017           Article No.         504763         504762         504761         504760           Transducer principle         Dynamic, closed         Frequency response         18 ~ 22000 Hz         20 ~ 20000 Hz           Sound Pressure level         110 8(1 kHz / 1 V <sub>rms</sub> )         108 dB (1 kHz / 1 V <sub>rms</sub> )         1 × 4 ms single-sided 0FC cable with 3.5 mm gold adaptor         22 Ω           THD         <0.1 % (1 kHz / 100 dB)         < 0.1 % (1 kHz / 100 dB)         1.4 m single-sided 0FC cable with 3.5 mm gold straight plug / 6.3 mm gold adaptor plug         1.4 m single-sided 0FC cable with 3.5 mm gold straight plug / 6.3 mm gold adaptor plug         1.4 m single-sided 0FC cable with 3.5 mm gold straight plug / 6.3 mm gold adaptor plug         204 x 93 x 240 mm         204 x 93 x 240 mm           Dimension of product packaging (Wx Hx D)         204 x 93 x 240 mm         204 x 93 x 240 mm         204 x 93 x 240 mm           Dimension of outer master carton (Wx Hx D)         425 x 305 x 263 mm         425 x 305 x 263 mm         425 x 305 x 263 mm		ND 429		UD 413	
UPC         615104218048         615104218031         615104218024         615104218017           Article No.         504763         504762         504761         504760           Transducer principle         Dynamic, closed         Dynamic, closed         Dynamic, closed           Frequency response         18 − 22000 Hz         20 − 20000 Hz         108 dB (1 kHz / 1 V <sub>ms</sub> )         40.1 % (1 kHz / 100 dB)         108 dB (1 kHz / 1 V <sub>ms</sub> )         40.1 % (1 kHz / 100 dB)         40.1 % (1 kHz / 100 dB) <th></th> <th>Version West</th> <th>Version East</th> <th>Version West</th> <th>Version East</th>		Version West	Version East	Version West	Version East
Article No.         504763         504762         504761         504760           Transducer principle         Dynamic, closed         Dynamic, closed           Frequency response         18 - 22000 Hz         20 - 20000 Hz           Sound Pressure level         110 dB (1 kHz / 1 V <sub>rms</sub> )         108 dB (1 kHz / 1 V <sub>rms</sub> )           Impedance         32 Ω         32 Ω           THD         <0.1 % (1 kHz / 100 dB)	EAN	4044155071597	4044155071580	4044155071573	4044155071566
Transducer principleDynamic, closedDynamic, closedFrequency response18 – 22000 Hz20 – 20000 HzSound Pressure level110 dB (1 kHz / 1 V <sub>ms</sub> )108 dB (1 kHz / 1 V <sub>ms</sub> )Impedance32 Ω32 ΩTHD<0.1 % (1 kHz / 100 dB)<0.1 % (1 kHz / 100 dB)Cable / Plug3 m single-sided OFC cable with 3.5 mm gold straight plug / 6.3 mm gold adaptor plug1.4 m single-sided OFC cable with 3.5 mm gold straight plug / 6.3 mm gold adaptor plugDelivery includesHD 429 headphones, 6.3 mm adaptor plugHD 419 headphonesPackaging204 x 93 x 240 mm204 x 93 x 240 mmDimension of product packaging (W x H x D)204 x 93 x 240 mm425 x 305 x 263 mmAmount of products per outer master carton (W x H x D)66Languages on product packagingVersion West: English, French, Spanish, Portuguese, German, Italian, Dutch	UPC	615104218048	615104218031	615104218024	615104218017
Frequency response18 – 22000 Hz20 – 20000 HzSound Pressure level110 dB (1 kHz / 1 V <sub>rms</sub> )108 dB (1 kHz / 1 V <sub>rms</sub> )Impedance32 Ω32 ΩTHD<0.1 % (1 kHz / 100 dB)	Article No.	504763	504762	504761	504760
Sound Pressure level110 dB (1 kHz / 1 Vrms)108 dB (1 kHz / 1 Vrms)Impedance32 Ω32 ΩTHD<0.1 % (1 kHz / 100 dB)	Transducer principle	Dynamic, closed		Dynamic, closed	
Impedance32 Ω32 ΩTHD<0.1 % (1 kHz / 100 dB)	Frequency response	18 – 22000 Hz		20 – 20000 Hz	
THD	Sound Pressure level	110 dB (1 kHz / 1 V <sub>rms</sub> )		108 dB (1 kHz / 1 V <sub>rms</sub> )	
Cable / Plug3 m single-sided OFC cable with 3.5 mm gold straight plug / 6.3 mm gold adaptor plug1.4 m single-sided OFC cable with 3.5 mm gold straight plugDelivery includesHD 429 headphones, 6.3 mm adaptor plugHD 419 headphonesPackagingDimension of product packaging (W x H x D)204 x 93 x 240 mm204 x 93 x 240 mmDimension of outer master carton (W x H x D)425 x 305 x 263 mm425 x 305 x 263 mmAmount of products per outer master carton66Languages on product packagingVersion West: English, French, Spanish, Portuguese, German, Italian, Dutch	Impedance	32 Ω		32 Ω	
Delivery includesHD 429 headphones, 6.3 mm gold adaptor plugHD 419 headphonesPackagingUnimension of product packaging (W x H x D)204 x 93 x 240 mm204 x 93 x 240 mmDimension of outer master carton (W x H x D)425 x 305 x 263 mm425 x 305 x 263 mmAmount of products per outer master carton66Languages on product packagingVersion West: English, French, Spanish, Portuguese, German, Italian, Dutch	THD	<0.1 % (1 kHz / 100 dB)		< 0.1 % (1 kHz / 100 dB)	
Packaging       Dimension of product packaging (W x H x D)     204 x 93 x 240 mm     204 x 93 x 240 mm       Dimension of outer master carton (W x H x D)     425 x 305 x 263 mm     425 x 305 x 263 mm       Amount of products per outer master carton     6     6       Languages on product packaging     Version West: English, French, Spanish, Portuguese, German, Italian, Dutch	Cable / Plug	<b>3</b>		<b>3</b>	
Dimension of product packaging (W x H x D)       204 x 93 x 240 mm       204 x 93 x 240 mm         Dimension of outer master carton (W x H x D)       425 x 305 x 263 mm       425 x 305 x 263 mm         Amount of products per outer master carton       6       6         Languages on product packaging       Version West: English, French, Spanish, Portuguese, German, Italian, Dutch	Delivery includes	HD 429 headphones, 6.3 mm adaptor plug		HD 419 headphones	
(W x H x D)     204 x 93 x 240 mm     204 x 93 x 240 mm       Dimension of outer master carton (W x H x D)     425 x 305 x 263 mm     425 x 305 x 263 mm       Amount of products per outer master carton     6     6       Languages on product packaging     Version West: English, French, Spanish, Portuguese, German, Italian, Dutch	Packaging				
(Wx H x D)     425 X 305 X 263 mm     425 X 305 X 263 mm       Amount of products per outer master carton     6     6       Languages on product packaging     Version West: English, French, Spanish, Portuguese, German, Italian, Dutch		204 x 93 x 240 mm		204 x 93 x 240 mm	
master carton 6  Languages on product packaging Version West: English, French, Spanish, Portuguese, German, Italian, Dutch		425 x 305 x 263 mm		425 x 305 x 263 mm	
		6		6	
	Languages on product packaging				

## **SENNHEISER**

## Sennheiser electronic GmbH & Co. KG

Am Labor 1, 30900 Wedemark, Germany www.sennheiser.com