Wireless sound experience.



RS 120 II



Enjoy wireless freedom.















ANT - CONTRACT

RS 120 II

The RS 120 II is an open, supra-aural wireless RF headphone system. Its transparent and well-balanced sound with great bass response makes this system an ideal choice for all types of music and TV applications. Furthermore, its innovative ,,easy recharge" function offers the ultimate in convenience when it comes to charging and storing your wireless headphones. Enjoy total freedom of sound, stylish design and maximum comfort, all at an affordable price.

- Detailed, warm sound reproduction with strong bass
- Suitable for all types of modern music and TV applications
- Wireless freedom with reception through walls and ceilings, up to 130 metres (430 feet)
- Volume and tuning controls conveniently located on the headphone
- Multi-functional transmitter with ,easycharge' function (transmitter, charging cradle and docking station)
- Optional wall mounting of transmitter







RS 110 II

The RS 110 II is an open, supra-aural wireless RF headphone system. Its transparent and well-balanced sound with great bass response makes this system an ideal choice for all types of music and TV applications. Enjoy total freedom of sound without a physically restricting cable at an affordable price. The ideal entry into the cordless world of sound.

- Detailed, warm sound reproduction with strong bass
- Suitable for all types of modern music and TV applications
- Wireless freedom with reception through walls and ceilings, up to 150 metres (500 feet)
- Volume and tuning controls conveniently located on the headphone
- Lightweight and comfortable

EAN UPC Artikel-Nr.

Transducer principle Ear coupling Frequency response Impedance THD at 1 kHz, 100 dB SPL SPL (1 kHz, 1 V_{rms}) Power supply Operating time Weight

Modulation Power supply

Power consumption Signal-to-noise ratio Connector Weight Dimension Frequency range No. of channels

Delivery includes

RS 110 II

4044155071788 615104218345 504775

HDR 110 II (Receiver)

Open, dynamic Supraaural 22 - 19,500 Hz 24 Ω < 0.7 % 106 dB 2 AAA cells 22 hours 230 g

TR 110 II (Transmitter)

FM, Stereo I/p: 100-240 V AC, 50-60 Hz, 0.1 A/o/p: 9V DC, 0.34 A, 3.06 W < 1.8 V > 65 dBA RCA phono plug, 3.5 mm / 6.3 mm stereo 180 g 85 x 110 x 133 mm 926.15 MHz - 927.55 MHz

HDR 110 II headphones TR 110 II transmitter 1 DC supply adapter 1 detachable audio cable 2 AAA rechargeable batteries Instruction manual

Packaging

Packaging design	recloseable cardboard box
Dimensions of Product packaging (H x W x D)	265 x 216 x 138 mm
Weight of product and packaging	0,99 kg
Dimensions of inner master carton (H x W x D)	740 x 480 x 310 mm
Total weight of inner master carton and products	13,40 kg
Amount of products in inner master carton	10
Languages	English, German, French, Italian, Spanish, Netherlands, Portuguese

RS 120 II

4044155071825 615104218413 504779

HDR 120 II (Receiver)

Open, dynamic Supraaural 22 - 19,500 Hz 24 Ω < 0.7 % 106 dB 2 AAA cells 20 hours 230 g

TR 120 II (Transmitter)

FM, Stereo I/p: 100-240 V AC, 50-60 Hz, 0.1 A/o/p: 9V DC, 0.34 A, 3.06 W < 1.8 V > 65 dBA RCA phono plug, 3.5 mm / 6.3 mm stereo 200 g 85 x 225 x 133 mm 926.15 MHz - 927.55 MHz

HDR 120 II headphones TR 120 II transmitter 1 DC supply adapter 1 detachable audio cable 2 AAA rechargeable batteries Instruction manual

recloseable cardboard box 307 x 214 x 138 mm 1,05 kg

740 x 480 x 350 mm

14,08 kg

10

English, German, French, Italian, Spanish, Netherlands, Portuguese